

# HIGH PRECISION PRESSURE CALIBRATOR

MODEL : PCAL 1300/1



Carrying case



## INTRODUCTION

Exact pressure measurement and monitoring are must in applications crucial to operational safety of machinery and industrial installations.

Regular inspection of the pressure gauges / sensor / transmitters / indicators used in these applications is absolutely essential for economic and technical - safety reasons and is already prescribed as obligatory in many sectors.

## APPLICATIONS

- Energy - Production and energy -Distribution sectors
- Glass, Ceramic, Semi conductor industries
- Steel material processing industries
- Calibrators laboratories etc.,.

## Descriptions

“SANSEL” PCAL 1300 / 1 is a Micro controller based precision pressure calibrators generates true reference pressure. Connect the gauge to be calibrated in the calibrator. Set the pressure using respective pump when stabilization.

## Specifications Technical Data

Features	Values
Model	PCAL 1300 / 1 mbar
Range (bar)	- 0.9 to 1 bar
Pressure media	Air
Pressure pump	HP - 04
Display	128 x 64 COG Graphic LCD with White LED Back light
Pressure Port	2 x ¼”BSP Female
Pump dimension in mm (Approx.)	170 x 45 (Height x Dia)
Resolution (bar)	6 digit user selectable
Instrument Port	¼ BSP Male x 10 mm long
Instrument dimension	100 x 100 x 55 (W x H x D) mm
Instrument Weight	400gms (Approx.)
Stability time	1 to 2 mins
Accuracy	± 0.05%FS
Pressure units * (selectable)	bar, mbar, Mpa, kpa, kg/cm <sup>2</sup> , inHg, cmHg, mmHg, mH <sub>2</sub> O, ftH <sub>2</sub> O, inH <sub>2</sub> O, cmH <sub>2</sub> O, mmH <sub>2</sub> O
Pressure Zero	One touch zero provided on front key
Pressure Peak	Maximum & minimum with user reset option
Pressure overflow	FS X 2 (Max.)
Pressure burst	FS X 3 (Max.)
Temp. Measure	RTD -PT 100 (2,3,4, wire selectable)
Temp. Range	-199.999 to 850.000
mA Measure	0-24 mA (scalable)
Display scale	-99999 to 99999 counts (for mA measure input)
Switch test	Provided
Display Hold	One touch hold provided on front key
Power Supply	9V DC ±5% / 200mAh Rechargeable battery with battery life 4hours with out back light( or) 9V DC adapter /230V AC supply operated
Pump Weight (gms)(Approx.)	700 gms
Pc Interface	RS 485
Pc Software	Windows based semi automatic calibration software (optional)

Note: Above Specification change without notice \*factory selected units are display which supports to pressure range

(P.T.O)

## Pneumatic Low Power Hand Pump

<b>Model</b>	<b>HP- 04</b>
<b>Pressure Range</b>	<b>-0.95 to 2 bar</b>
<b>Pressure Media</b>	<b>Air</b>
<b>Pressure Outlet Port</b>	<b>2 x ¼ ” BSP Female</b>
<b>Stability</b>	<b>1 to 2 mins</b>
<b>Weight (Approx.)</b>	<b>700g</b>
<b>Dimension L X H XW</b>	<b>170mm Height x 45 mm dia (Approx.)</b>

### Standard Delivery

1. 9V DC Battery charger
2. 9V DC Re-chargeable battery
3. AC to DC adapter
4. Calibration certificate

### Optional

1. Pressure / Vacuum pump
2. Set of adopters
3. Temperature sensors
4. Carrying case
5. NABL Calibration certificate

## SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879  
( Thermal, Mechanical, Electro-Technical, Dimension Parameters )

1 / 46 , 3<sup>rd</sup> Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA  
☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📞 +91 98401 49928 ✉ enquiry@ sansel.net

