


HIGH PRECISION PRESSURE CALIBRATOR

MODEL : PCAL 1300 / 350



Carrying case



INTRODUCTION

Exact Pressure Measurement and Monitoring are Must in Applications Crucial to Operational Safety of Machinery and Industrial Installations.

Regular Inspection of the Pressure gauges / sensor / transmitters / indicators Used in these Applications is Absolutely Essential for Economic and Technical - Safety Reasons and is Already Prescribed as Obligatory in Many Sectors.

APPLICATIONS

- Energy - Production and Energy -Distribution Sectors
- Glass, Ceramic, Semi Conductor Industries
- Steel Material Processing Industries
- Calibrators laboratories etc.,.

Descriptions

“SANSEL” PCAL 1300 / 350 is a Micro controller Based Precision Pressure Calibrators Generates True Reference Pressure. Connect the gauge to be Calibrated in the Calibrator. Set the Pressure using respective pump when stabilization.

Specifications Technical Data

Features	Values
Model	Pcal 1300 / 350 bar
Range (bar)	0 to 350 bar
Pressure media	Oil & Water
Pressure pump	HP – 02A
Display	128 x 64 COG Graphic LCD with White LED Back light
Pressure Port	2 x ½” BSP Female
Pump dimension in mm (Approx.)	310 x 80 x 165 (L x H x W)
Resolution (bar)	6 digit user selectable
Instrument Port	¼ BSP Male x 10 mm long
Instrument dimension	100 x 100 x 55 (W x H x D) mm
Instrument Weight	400gms (Approx.)
Stability time	1 to 2 mins
Accuracy	± 0.05%FS
Pressure units * (selectable)	bar, mbar, Mpa, kpa, kg/cm ² , inHg, cmHg, mmHg, mH ₂ O, ftH ₂ O, inH ₂ O, cmH ₂ O, mmH ₂ O
Pressure Zero	One touch zero provided on front key
Pressure Peak	Maximum & minimum with user reset option
Pressure overflow	FS X 2 (Max.)
Pressure burst	FS X 3 (Max.)
Temp. Measure	RTD -PT 100 (2,3,4, wire selectable)
Temp. Range	-199.999 to 850.000
mA Measure	0-24 mA (scalable)
Display scale	-99999 to 99999 counts (for mA measure input)
Switch test	Provided
Display Hold	One touch hold provided on front key
Power Supply	9V DC ±5% / 200mAh Rechargeable battery with battery life 4hours with out back light(or) 9V DC adapter /230V AC supply operated
Pump Weight (gms)(Approx.)	1850
Pc Interface	RS 485
Pc Software	Windows based semi automatic calibration software (optional)

Note: Above Specification change without notice *factory selected units are display which supports to pressure range

(P.T.O)

Hydraulic high pressure pump

Model	HP- 02A
Pressure Range	0 to 350 bar
Pressure Media	Hydraulic 68 grade oil & other oil (optional water)
Pressure Outlet Port	2 x ½” BSP Female thread for UUT & Master
Stability	1 to 2 mins
Weight (Approx.)	1850 gms
Dimension L X H X W	310 x 80 x 165 mm (Approx.)

Standard Accessories

1. 9V DC Battery charger
2. 9V DC Re-chargeable battery
3. AC to DC adapter
4. Calibration certificate

Optional

1. Pressure / Vacuum pump
2. Set of adopters
3. Temperature sensors
4. Carrying case
5. NABL Calibration certificate

SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879
(Thermal, Mechanical, Electro-Technical, Dimension Parameters)

1 / 46 , 3rd Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA
☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📞 +91 98401 49928 ✉ enquiry@ sansel.net

