

MINIATURE (BABY) DRY BLOCK TEMPERATURE CALIBRATOR

For Thermocouple & RTD Sensor Calibration
MODEL : TCAL 1402 / 300

First time
in INDIA
Miniature Bath

Right Product for
your Calibration
need



See the actual size
(Comparison with pencil)

INTRODUCTION

SANSEL Model TCAL 1402 / 300 Miniature calibrator bath are one of the smallest dry well calibrator in the world, which are ideally suited were necessary for fast calibration in process industries to calibrate Thermocouple, RTD, Indicator with sensor & transmitter with sensor.

Temperature range of the TCAL 1402 / 300 covers from Ambient + 5°C to 300°C. These equipment are light weight, fast raising, quick settling, better stability & uniformity.

TCAL 1402 / 300 Miniature calibrator bath's temperature are adjusted simply using 4 keys on the controller, can be very quickly controlled the actual and set temperature can be displayed simultaneously on a 4+4 digit high brightness LCD.

TCAL 1402 / 300 having interchangeable inserts to suit for calibration of different diameter of sensors (upto 20mm). Additional inserts (optional) with special drillings are available to order.

FEATURES

- ✓ Wide temperature range Amb to 300°C
- ✓ Light weight - Less than 2 kg (Approx.)
- ✓ World class performance
- ✓ Fast calibration save time & money
- ✓ Simple, Convenient & easy operation
- ✓ High Bright LCD Display
- ✓ Rugged & most compact for onsite carry
- ✓ Inter changeable insert to suit different diameter sensor
- ✓ Supplied with rexein carry bag
- ✓ ISO / IEC 17025 Standard Accredited Calibration Certificate

Technical Specifications

Model	TCAL 1402 / 300
Display	0.58" (15mm)(Block) / 0.3"(7.8mm) (Set) 4 digit LCD Display with 4 keys
Temperature Range	Amb. to 300°C
Radial uniformity	± 0.3°C
Resolution	0.1°C
Stability	± 0.1°C
Temperature readout	°C
Heating time	25 °C / minute
Cooling time	15 minutes (300 To 100 °C)
Stabilization time	3 minutes
Well Dimension(dia. x height)	20 x 100 mm
Well immersion depth	80 mm
Standard well hole	6.2, 6.2
Power supply	230V AC ± 10% / 50Hz (Optional 110V AC)
Power consumption	500 VA
Overall Dimension in mm	150 x 90 x 190 (L x B x H)(Approx.)
Instrument Weight	2 kg (Approx.)

Note: Due to continuous product improvements, Published specifications may change with out notice

Standard Delivery

1. Basic Instrument
2. Spare fuses
3. Carry bag
4. Well tool
5. Instruction manual
6. Mains card
7. Standard well insert
8. Traceable calibration certificate

Optional

1. Master Indicator with sensor
2. Additional well insert
3. Carrying case



Carry bag

SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879

(Thermal, Mechanical, Electro-Technical, Dimension Parameters)

1 / 46 , 3rd Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA

☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📠 +91 98401 49928 ✉ enquiry@ sansel.net

🌐 www.sansel.net

🌐 www.sansel.in

🌐 www.sansel.co.in

🌐 www.calibrators.in

